MySql password and old_password

```
/* Old password type */
SET PASSWORD FOR 'some_user'@'some_host' = OLD_PASSWORD('mypass');
/* New password type */
SET PASSWORD FOR 'some_user'@'some_host' = PASSWORD('mypass');

ALTER USER 'root'@'localhost' IDENTIFIED WITH mysql_native_password  BY
'mypass';
```

'mysql_native_password' is deprecated and will be removed in a future release. Please use caching_sha2_password instead

```
SHOW VARIABLES LIKE 'validate_password%';
+--------------------------------------+-------+
| Variable_name                        | Value |
+--------------------------------------+-------+
| validate_password.check_user_name    | ON    |
| validate_password.dictionary_file    |       |
| validate_password.length             | 6     |
| validate_password.mixed_case_count   | 1     |
| validate_password.number_count       | 1     |
| validate_password.policy             | LOW   |
| validate_password.special_char_count | 1     |
+--------------------------------------+-------+
SET GLOBAL validate_password.length = 6;
SET GLOBAL validate_password.number_count = 0;
```

From:
https://wiki.plecko.hr/ - **Eureka Moment**

Permanent link:
https://wiki.plecko.hr/doku.php?id=database:mysql:password

Last update: **2025/06/26 13:38**