Debian set proxy

Edit /etc/profile.d/proxy.sh, add

```
export http_proxy=http://192.168.0.1:3128
export https_proxy=http://192.168.0.1:3128
export ftp_proxy=http://192.168.0.1:3128
```

Edit /etc/apt/apt.conf.d/99HttpProxy, add

```
Acquire::http::Proxy "http://192.168.0.1:3128";
Acquire::https::Proxy "http://192.168.0.1:3128";
Acquire::ftp::Proxy "http://192.168.0.1:3128";
```

Edit /etc/wgetrc, add

```
http_proxy = http://192.168.0.1:3128
https_proxy = http://192.168.0.1:3128
ftp_proxy = http://192.168.0.1:3128
```

Edit /etc/environment

```
export http_proxy=http://192.168.0.1:3128
export https_proxy=http://192.168.0.1:3128
export ftp_proxy=http://192.168.0.1:3128
```

some system commands rely on wget, and may not otherwise use an environment variable, e.g. debootstrap; the http_proxy setting should be present by default but commented out.

This is all, in a round about way, relayed to the http proxy security vulnerability announced in July 2016 – see httpoxy.org for more info.

From:
https://wiki.plecko.hr/ - **Eureka Moment**

Permanent link:
https://wiki.plecko.hr/doku.php?id=linux:networking:proxy

Last update: **2019/10/31 09:05**