

# Docker

## run

```
docker run -d --restart=always -p <host port>:<container port> -v  
<volume> --name <container name> <image name>:<optional version>  
# run => pull and start in one command  
# -d => detach on run  
# --restart => always restart the container. Defaults to 'no'  
# -p => publish port  
# -v => volume list  
# --name => assign a name to the container
```

## pull + run

```
docker pull <image name>  
docker pull pengbai/docker-supermario  
docker run -d -p 8765:8080 --name mario pengbai/docker-supermario
```

## volumes

```
# data in container is reset on container stop  
  
# anonymus volume  
docker run -d --restart=always -p <host port>:<container port> -v  
/app/data --name uptime-kuma louislam/uptime-kuma:1  
  
# mount physical directory  
docker run -d --restart=always -p <host port>:<container port> -v  
/home/mount/data:/app/data --name uptime-kuma louislam/uptime-kuma:1  
  
# create a volume and mount it (perferred choice)  
docker volume create uptime-kuma  
docker run -d --restart=always -p <host port>:<container port> -v  
uptime-kuma:/app/data --name uptime-kuma louislam/uptime-kuma:1
```

## basic commands

```
# access container shell  
docker exec -it 6f7d8322947c bash  
  
# stop container and delete it  
docker stop <container id>  
docker rm <container id>  
  
# delete local image
```

```
docker rmi <image id>
```

### Dockerfile example

```
FROM ubuntu
MAINTAINER Tomislav Plečko, tomislav@plecko.hr

RUN apt update
RUN apt -y install libicu-dev libssl-dev

RUN mkdir /app
COPY Vacation /app
RUN chmod +x /app/dotnet
RUN cd /app

# ENV DOTNET_SYSTEM_GLOBALIZATION_INVARIANT=1

WORKDIR /app

CMD ["/app/dotnet", "/app/NoticeVacation.dll", "--vacation"]

#ENTRYPOINT /app/dotnet /app/NoticeVacation.dll --zulip
```

From:  
<https://wiki.plecko.hr/> - **Eureka Moment**

Permanent link:  
<https://wiki.plecko.hr/doku.php?id=linux:software:docker>

Last update: **2022/03/01 13:09**

